Inline Extraction Kits - Ready for Contour Fascia Selection

These kits are designed so that the interior grille can be mounted directly above your steam source (e.g. shower or bath). The adapter unit has a comprehensive range of stylish, interchangeable fascia to choose from.

A 150mm duct connecting ceiling plenum, with 90° ovalised moulded plastic elbow outlet and back-flow preventer for unimpeded airflow, is also available as a separate alternative option to the adapter unit. 5 year warranty.

Designer Standard Profile	Duct (mm)	Fan Type	Max. Fan Watts	Max. Fan Pressure	Free Air Fan Performance		Specific Fan Power	Fascia	Exterior Grille	Switching	Order Code
Standalu Pione	(11111)	туре	(W)	(Pa)	(l/s)	(m³/hr)	(W/I/s)		unite		Code
	150	Mixed Flow	70 60	300 240	166 92	597 330	0.42 0.65	Range Selection	White Fixed Louvre	Standard	FAN7366
90	150	EC Axial	18	91	105	380	0.17	Range Selection	White Fixed Louvre	Standard	FAN7044

Note: Installed system performance is always influenced by duct length and layout

Switching Options

Standard Remote switch (not supplied).

Fascia Selections

Adapter Plate		Ro	und		Square				
supplied with kits above	White	Black	LED White	LED Black	White	Black	LED White	LED Black	
	\bigcirc	0	\bigcirc	0					
DCT4500	DCT4502	DCT4503	DCT4506	DCT4507	DCT4504	DCT4505	DCT4508	DCT4509	
Ceiling Plenum		Ro	und		Square				
(order separately)	White	Black	LED White	LED Black	White	Black	LED White	LED Black	
-	\bigcirc	0	\bigcirc	0					
					DCT4504				

• Fascias are a stylish super low profile slim line design available in white or black

- 10W LED light panel fascia options include driver with quick connection 12V plug and pre-fitted 240V AC supply lead and plug ٠
- Fascias are easy to install, remove and clean

Inline Extraction Kits - Ready for Contour Fascia Selection


Dimensions (mm)


Model	Α	В	C	D	E	F	G
FAN7366	209	147	360	55	195	130	115
FAN7044	200	143	170	185		-	
Adapter Plate	75	265			-		
Ceiling Plenum	196-167 (adjustable)	265	190	103		-	
Round Fascia	272				-		
Square Fascia	272	272			-		

Ц


R

ΤÞ











Adapter Plate

R

Fascias






120

Model	FAN7366	FAN7044	LED Fascia				
Supply	220-240V AC, 50Hz						
Sound Level	40/47dB(A)	38 dB(A)	-				
Max. Operating Temp		45°C	-				
Wattage	60-70W	18W	10W				
Light		-	850 lm				
LED Colour		-	42000K				
IP Rating		IP44					

Ceiling Plenum



www.simx.co.nz