



Aquatika Warranty

Aquatika NZ Limited offer the following warranty periods on its range of tapware from the date of purchase.

Residential Use

- Tapware - 5 year warranty
- Handshowers, Shower Roses – 2 year warranty
- Pull-out Sprays and spray heads on Sink Mixer Coils – 2 year warranty
- Commercial tapware – 2 year warranty

Commercial Use

- Tapware - 1 year warranty
- Handshowers, Shower Roses – 1 year warranty
- Pull-out Sprays and spray heads on Sink Mixer Coils – 1 year warranty

Only high quality workmanship and materials have been used in the manufacture of Aquatika's tapware. If any workmanship or material is proven faulty during the warranty period, Aquatika NZ Limited will, at its own cost or option, repair or replace the faulty product.

The warranty is transferable but the original proof of purchase from an authorised Aquatika distributor is required for all claims.

Aquatika's liability will not extend to damage caused by reasonably foreseeable loss such as inappropriate materials in a wet area ie. floating wooden floors.

Waterlines to tapware incorporating a ceramic cartridge or ceramic disc mechanism should have an inline strainer or filter fitted. Absence of these may void the warranty.

Any suspected defect must be notified to Aquatika as soon as possible after discovery. All repair work must be performed by a plumber who has received authorisation from Aquatika prior to proceeding with the work. Aquatika may immediately authorise repair work to be undertaken, however, this is not necessarily acceptance of liability.

Aquatika guarantee that the tapware will be able to handle temperatures up to a maximum of 80°C.

Water pressure up to 1000 kPa is the maximum limit for the tapware. Above this the warranty will become void.

Serial numbers or tags should not be removed from the products as they are essential in establishing warranty.

Aquatika NZ Limited

9 Saunders Place,
Avondale, Auckland.

Tel: 09-828 2068,
Fax: 09-828 2069

Email: info@aquatika.co.nz
or visit our website:

www.aquatika.co.nz

© copyright Aquatika 2016

Code: AN 1BASIN

Finish: Chrome

Mechanism: Standard European cast (Ceramic mechanisms available on request)

Spout: Chromed cast brass. Swivel 360°

- Normally supplied with 130mm (short) spout
- For large spout (approximately 30mm taller and 65mm longer reach) add SP NV SPOUT XXL to code

Body: Chrome plated brass

Handle: 4 winged, chrome plated, die cast zinc

Water Inlet: 1/2" BSP Thread: Male

Water Outlet: Casting

Mounting: Mounting Hardware: Stud: 8mm
Nut: 11mm A/F
Horseshoe Washer

Supplied with base seal - O-ring size:

Flow Control: PCA 7

Pressure Range: 20 - 600 kPa

Max water flow @ 35kPa = 19.5 l/min

Suitable for low/unequal & mains pressure systems

Recommended Operational Pressure Range: 20 - 600 kPa
Maximum Operating Temp: 80°C Never to Exceed: 1000 kPa

