

## Sanicondens® Pro

The Sanicondens® Pro is specifically designed for disposal of condensate from air conditioning units, refrigeration units, ice machines and dehumidifiers etc. Includes a non-return valve and 6 m flexible discharge pipe.



## WHY CHOOSE THIS PRODUCT?

2 L tank

Two entry points

Working temperature of 35°C.

Will handle temperatures up to 80°C for short periods (5 minutes)

Supplied with 2 m of electric cable and 6 m of discharge pipe

High level alarm connectivity

## **TECHNICAL CHARACTERISTICS**

Discharge Pipework	8/11 mm
Motor Power	60 Watts
Flow Rate	342 L/h
Voltages	220-240 V/50 Hz
Tank Volume	2 L
Working Waste Water Temp	35°C/Max 80°C (intermittent)
Product Weight	2 kg
Overall Measurements	260 x 169 x 143 mm
Inlet Pipework	25 mm
IP Rating	IP20



## **VERTICAL/HORIZONTAL PERFORMANCE**

4.5m	max 15m
↑ 4m	max 20m
↑ 3m ↑	max 30m
2m	max 40m
1m	max 50m
1	1%

260	143
242	( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( ) ( )
	691





REFRIGERATOR





PRODUCT REFERENCE: SA92



Shaking up water

Made in France to the highest standards, needs to be installed by a licensed plumber