

caroma®

NZ10/09

719100W

Date

October 2009

Supersedes all previous issues

Leda Care Invisi II Suite

4.5/3 litre Dual Flush Toilet Suite with
Leda 2000 Vitreous China Wall Faced Box Rim Pan and
Invisi II Smartflush Cistern - Inwall, Induct or Inceiling
applications for People with Disabilities.
Installations complying to A.S.1428-1




Leda Care Invisi II

**4.5/3 litre Dual Flush Toilet Suite with
Caroma Care Leda 2000 Vitreous China Wall Faced Pan
and Invisi II Smartflush Cistern for
Inwall, Induct or Inceiling applications.
For People with Disabilities.**



Installations Complying to the WC pan requirements A.S.1428-1

Leda Care Invisi II Smartflush 4.5/3 dual flush toilet suite uses Caroma Smartflush technology to deliver the latest water-saving technology in sanitaryware products and is designed to provide a raised seat height of between 460-480mm for persons with disabilities. For compliance to A.S.1428-1 it is necessary to locally extend the wall out to provide pan projection of 800mm \pm 10mm to the front of the pan. Concealed cistern and plumbing fittings provide space saving, ease of cleaning and performance matched components to maximise flushing efficiency.



Important:

Reference must be made to A.S.1428-1 with current amendments to determine circulation space, grab rail and installation requirements. The dimensions in this sheet may change with amendments to the standard.

Pan:

Caroma Care Leda 2000 4.5 litre full flush wash down box rim type.

Traps:

Universal trap.

Inlet:

50mm back inlet. A 40mm Key seal is available.

Cisterns:

Invisi II Cistern - suitable for inwall, induct and inceiling applications. For push button, access panel and plate options available refer to technical manual.

Seats:

The following seats are recommended: **Pedigree II Care, Colani** disabled and **Caravelle Care**.

Position of the Pan:

For wheel chair access the installed pan must be a minimum of 800 \pm 10mm from the front of the pan to the finished wall and provide a seat height of 460 to 480mm. For people with ambulant disabilities the pan can be fitted directly to the existing wall without the need to locally extend the wall.

Position of Cistern:

The pan is suitable for installation with concealed cisterns providing the circulation space requirement is maintained. The height of the push button must be no greater than 1100mm to the top of the push button and positioned within the push button zone or on the centre line of the pan.

Colour:

White only.

Installation:

The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.

Dimensions:

All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

Note: The projection requirements detail on this illustration are for wheel chair access only. The projection requirements for people with ambulant disabilities is 610 to 660mm.

Leda Care Invisi II Toilet Suite: Code No.

4.5/3 litre Back Inlet

Internal overflow

719100W

