caroma

NZ10/09 712100W

Date
October 2009

Supersedes all previous issues

Leda Invisi II Suite

4.5/3 litre Dual Flush Toilet Suite with Leda 2000 Smartflush Vitreous China Wall Faced Box Rim Pan and Invisi II Smartflush Cistern for Inwall, Under Counter, Induct or Inceiling applications







Leda Invisi II

4.5/3 litre Dual Flush Toilet Suite with
Leda 2000 Smartflush Vitreous China
Wall Faced Box Rim Pan and
Invisi II Smartflush Cistern for
Inwall, Under Counter, Induct or Inceiling applications





Leda Invisi II 4.5/3 litre dual flush toilet suite uses Caroma Smartflush technology to deliver the latest water-saving technology in sanitaryware products and features smooth sides and concealed plumbing fittings, which allow for varying setouts. The uni-connector pan connecting system allows for setout adjustments from 85mm to 120mm with a recommended setout of 90mm providing installation versatility for new and renovation applications. Suitable for domestic and commercial applications. Featuring concealed plumbing fittings with projection from wall of 610mm. Multiple button options are available to suit domestic and commercial applications. Concealed cistern and plumbing fittings provide space saving, ease of cleaning and performance matched components to maximise flushing efficiency.

Pan: Leda 2000 Smartflush 4.5 litre full flush partial box rim pan.

Traps: Universal trap for S or P-trap installations.

Cistems: Invisi II Smartflush Cistern - suitable for inwall, under counter, induct and inceiling

applications. For push button and access plate (supplied separately) options refer to

technical manual.

Fixing: Pan is supplied with D.80 Concealed Pan Fixing Bracket.

Cistern is simply mounted into position by clipping onto the two quick clip mounting brackets which are secured with screws to the studwork or induct brickwork. Cistern

brackets and flush pipe supplied.

Seats: Includes Pedigree II seat.

Colours: White only.

Installation: The installation of the toilet suite shall be in accordance with the normal minimum

drainline grade requirements in AS/NZS 3500.2.

Dimensions: All dimensions are in millimetres and are subject to normal manufacturing variations.

Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

