

MANROSE CLASSIC WINDOW MOUNTED FANS

WF MODELS

STANDARD MODELS

Duct Size	Model	Switching	Performance	Order Code
100mm	WF100P	Pull Cord	23 l/s, 85m ³ /hr	FAN0021
100mm	WF100PLV	Low Voltage	23 l/s, 85m ³ /hr	FAN5884

12VAC transformer included with LV switching models and suitable for installation in damp areas, zones 1, 2 and 3.

AUTO SHUTTER MODELS

Duct Size	Model	Switching	Performance	Order Code
150mm	WF150AP	Pull Cord	87 l/s, 313m ³ /hr	FAN0107
150mm	WF150APT	Pull Cord Timer	87 l/s, 313m ³ /hr	FAN0109
150mm	WF150APLV	Low Voltage	87 l/s, 313m ³ /hr	FAN5897

Electrically operated louvre shutters open automatically when fan is running - prevents back-draughts.

12VAC transformer included with LV switching models and suitable for installation in damp areas, zones 1, 2 and 3.

- Designed for use in situations where an existing window fan is being replaced or where there is no available external wall space or ceiling space access.
- These axial fans have ball bearing motors to prolong the life of the motor.
- Supported by a 5 year warranty.



Standard Models



Auto Shutter Models

Switching Options

1. Timer - Fan operates from a switch and continues to run for a preset time after switching off - adjustable 1-20 minutes.

2. Pull Cord - Integral pull cord switch on fan..

NOTE: All fan flow rates quoted are free air delivery.